

Scrimless Non-Curling Blockout Banner

PRODUCT: C-Flat- Blockout

FEATURES / APPLICATIONS:

- Super smooth surface makes it perfect for high resolution printing
- High opaque banner material
- Non curling appearance at the edge
- Perfect for double sided signs and banners
- Desired for pop-up or roll-up systems, POP and hanging banners
- Suitable for indoor or low stress outdoor advertisement

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
STD Width	N/A	0.914/1.07/1.10/ 1.37/ 2.2/	36" /42" /43" /54" /87" /126"
STD Length	N/A	50m	55yd
Weight	DIN EN ISO 2286-2	510g/sq.m	15oz/sq.yd
Support Material	DIN 60001		PET
Coating	DIN 60001		PVC
Tensile Strength	DIN EN ISO 1421	1182 x1173N/5cm	133 x 132 lbs/inch
Tear Strength	DIN 53363	34x27N/5cm	7.6x6.0lbs/inch
Temperature Resistance	N/A	- 20~70°C	-4~158°F

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Screen Printing	Dye Transfer	Dye Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of warranty

CGS Imaging Inc.

6950 Hall Street
Holland Ohio 43528
www.cgs-imaging.com

P. 419.897.3000
F. 419.893.4316