

18oz PREMIUM POLE BANNER BLOCKOUT

PRODUCT: BLO-610PB

FEATURES / APPLICATIONS:

- 1000DX1000D, 12X12 base fabric makes it more stable, can reduce the wavy problem effectively;
- 35% stronger than the normal 9x9 blockout, ideal for long-term outdoor use;
- Super smooth surface on both sides for high resolution printing;
- Perfect opacity makes it printable on both sides with uniform quality.

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	610 g/sq.m	18 oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Thickness	ASTM D751-2006	0.43mm	16.9mil
Yarn Dtex	DIN EN ISO 2060	1100x1100 dtex	1000x1000 denier
Tensile Strength	DIN EN ISO 1421	1713x1442 N/5cm	196x165 lbs/inch
Tear Strength	DIN 53363	443x283N	99x64lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	N/A	NFPA 701, DIN4102-B1	
Width	ASTM D751-2006	Max 320cm	126"
Standard Length	ASTM D751-2006	50m	55yd

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of Warranty

CGS Imaging Inc.

6950 Hall Street
 Holland Ohio 43528
www.cgs-imaging.com

P. 419.897.3000
 F. 419.893.4316