

**9oz/ 300gsm Supreme Mesh**

**PRODUCT: MESH-189**

**FEATURES / APPLICATIONS:**

- 25% air-flow through
- Printable on two sides with UV ink
- Offer enhanced image compared to traditional meshes
- Suitable for large format advertisement
- Widely used for scaffolding, theatrical, wall wrapping, TV backdrops, hanging display & large format advertisement
- A PVC backing is also available which prevents ink spray through when printing and makes the

**MATERIAL DETAILS**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	300g/m <sup>2</sup>	9oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1800x1440N/5cm	202x162 lbs/Inch
Tear Strength	DIN 53363	290x248N	65x 56lbs
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 500cm	197 inch

**INK PRINTABILITY**

Solvent	Eco Solvent	UV	Latex
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose warranty

**CGS Imaging Inc.**

6950 Hall Street  
Holland Ohio 43528  
[www.cgs-imaging.com](http://www.cgs-imaging.com)

**P. 419.897.3000**  
**F. 419.893.4316**