

## POPULAR FLAG


**PRODUCT:** ST-110T/ST-110D

### FEATURES

- 100% polyester texturized warp-knitted fabric, semi-matte
- It makes an excellent double penetration effect after Dye-sub printing

### APPLICATIONS:

- Flags



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	110 g/sq.m	3.2 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted 3 bar	
Shrinkage	N/A	≤ 2% ( 210°C, 30s )	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°c -210°c , 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥ 210°c	
Width	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	100m	110yds

### INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye Transfer	Dye Direct	
	<input type="checkbox"/>	<input type="checkbox"/>	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of warranty.

**CGS Imaging Inc.**

6950 Hall Street  
Holland Ohio 43528

[www.cgs-imaging.com](http://www.cgs-imaging.com)

P. 419.897.3000

F. 419.893.4316