

### 6oz/ 210gsm SPEAKER MESH

PRODUCT: SPEAKER MESH

FEATURES: APPLICATIONS

- A special design to maximize the overall cost
- 80% air -flow through
- Printable on two sides with UV ink
- Excellent printing result
- Widely used for scaffolding, theatrical, TV backdrops, hanging display& large format advertisement
- A PVC backing is also available which prevents ink spray through when printing and makes the feeding easier

#### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	210g/m <sup>2</sup>	6oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1100x950N/5cm	123x107 lbs/inch
Tear Strength	DIN 53363	250x200N	56x 45lbs
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 500cm	197 inch

#### INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of warranty

### CGS Imaging Inc.

6950 Hall Street  
Holland Ohio 43528  
[www.cgs-imaging.com](http://www.cgs-imaging.com)

P. 419.897.3000  
F. 419.893.4316